

V8

Networked Multifunction Receiver for Geophysical Techniques

- Flexible, adaptable configurations
- Lightweight, highly portable
- Operates -20°C to $+50^{\circ}\text{C}$
- No cable links required between network units or transmitter
- Cable or wireless link to local network of auxiliary units
- GPS-synchronized to transmitter and local network

MT, AMT	Magnetotellurics with remote reference
CSAMT	Controlled Source Audio MT
IP	Induced Polarization: Frequency and Time Domain, Phase and Spectral IP
TDEM, FDEM	All common Time and Frequency Domain Electromagnetics functions
Resistivity	All common Resistivity functions (Dipole, Schlumberger, or Wenner soundings)
Other	Record or monitor time series data from any suitable sensor, including geophones



Wireless networking with RXU-3ER receivers and RXU-TMR transmitter controller



V8 Multifunction Receiver

The V8 is the eighth generation of receiver technology developed by Phoenix since 1975.

The V8 builds upon many of the most attractive features of the highly successful Phoenix V5, V6A, and *System 2000*, including permanent GPS synchronization and light weight. The full-size ASCII keyboard and full-size, full-colour, sunlight-readable display give the operator hands-on control of the

entire data acquisition process for all the most common geophysical techniques—both controlled source techniques and natural source techniques (AMT, MT).

The V8 has 3 magnetic channels and 3 electric channels. The magnetic channels can be assigned either to standard magnetic sensors or to TDEM sensors. The V8 can operate in stand-alone mode (usually for AMT and MT). In addition, it can serve as the hub of a local network of

auxiliary 3-channel (3E) data acquisition units, which communicate with the V8 by wireless or optional cable.

All recording units are permanently synchronized to GPS time and are optimized to operate with transmitters similarly synchronized and controlled by the RXU-TMR auxiliary unit. No cable links are required between the networked recording units, or between receivers and the RXU-TMR/transmitter pair.

Applications

Exploration—surface to 50 km or more...

- Oil and gas
- Metals and minerals
- Groundwater
- Kimberlites (diamonds)
- Geothermal reservoirs
- Monitoring
- Earthquake research
- Engineering and environmental

Summary Specifications

Channels	3 Magnetic 3 Electric Unlimited number of optional 3-channel auxiliary units (RXU-3)
Frequency Range	10 000Hz to 0.00005Hz (20 000s)
Data Storage	On-board removable flash memory, 512MB (upgradeable)
ADC	One per channel 24 bits, 96 000 samples/s (main channels)
Weight	7kg
Keyboard	Full ASCII
Display	640 x 480 full-colour sunlight-readable TFT-LCD with backlight, power-save indicator
Connectors	Multi-pin, military-style connectors for sensor input, GPS, battery and ground connectors Four panel-mounted binding posts for electric field inputs (AMT, MT)
Input power	12V DC
Power consumption	15 watts approx.
Processor	DM&P Vortex86SX and auxiliary processors
Environmental	Operating: -20°C to +50°C

© 2012 Phoenix Geophysics Limited



PHOENIX Geophysics Limited

3781 Victoria Park Avenue, Unit 3

Toronto, ON, M1W 3K5 CANADA

www.phoenix-geophysics.com

☎: +1 (416) 491-7340

☎: +1 (416) 491-7378

✉: mail@phoenix-geophysics.com

Specification version 3.1, July, 2012. Subject to change without notice.